



Short survey of the LSA-PLUS 201 and 220

The KRONE LSA-PLUS 201 and 220 boxes have been specifically designed for use in indoor telephone wiring systems.

The 201 series is designed to accommodate up to 20 pairs and the 220 series can connect (or terminate) up to 30 pairs.

These boxes come with deep lids and can be additionally fitted with overvoltage protection.

Technical specifications

■ Materials

Series 201: Lustran 1170
HB according to UL 94, IEC 707

Series 220: Bayblend FR 90
V-0 according to UL 94, IEC 707

Order No.	Description	Capacity	Equipped with
6429 1 024-00	Mini distributor 201 C	10 pairs	one LSA-PLUS connection module 1/10 (120 x 170 x 35mm)
6429 1 016-00	Mini distributor 201 C	20 pairs	two LSA-PLUS connection module 1/10 (120 x 170 x 35mm)
6429 1 078-00	Mini distributor 201 D	10 pairs	one LSA-PLUS disconnection module 2/10 (120 x 170 x 43mm)
6429 1 078-00	Mini distributor 201 D	20 pairs	two LSA-PLUS disconnection module 2/10 (120 x 170 x 43mm)
6429 1 074-00	Mini distributor 201 D	20 pairs	two LSA-PLUS disconnection module 2/10 (120 x 170 x 80mm) Retrofitting of overvoltage protection is possible.
6429 1 073-01	Mini distributor 220 D	30 pairs	Empty housing with integrated back-mount frame for 3 modules 2/10 (120 x 170 x 80 mm) Retrofitting of overvoltage protection is possible.